

Agilent N7711A, N7714A Tunable Laser Sources

Data Sheet
Version 1.0



Agilent Technologies

Introduction

The Agilent N7711A and N7714A tunable lasers are single-port and four-port sources, available with C-band or L-band wavelength coverage. The narrow linewidth and offset grid fine-tuning capability of the N7711A and N7714A make them ideal sources for realistic loading of the latest transmission systems.

To owners of Agilent's proven Lightwave Measurement System the 81950A tunable laser source module offers the same features as the N7711A. The 81950A plugs into the 8163B and 8164B mainframes. For additional information about the 81950A please refer to the Compact Tunable Laser data sheet, publication no. 5988-8518EN.

Operation Modes

All models can reach any wavelength point within their specified wavelength range just like all other Agilent tunable lasers. In this mode, code compatibility with existing test setups based on Agilent's range of full-size and compact tunable lasers is a great asset.

In system loading applications, it may be preferable to grid-tune the lasers like system transmitters, simply by changing the channel index. The channel grid is adjustable to standard ITU-T grid spacing like 50 GHz, and to arbitrary grids. Likewise, the zero frequency (base channel) of the chosen grid is adjustable. A 12 GHz fine-tuning range allows de-tuning the frequency.

Key specifications and features

- Compact instrument format with one or four ports per unit on one-half 19-inch width and one-unit height;
- Flexible configuration of four-port model between C- and L-band channels (N7714A);
- Adjustable to any wavelength grid (ITU-T 100 GHz, 50 GHz, 25 GHz, and arbitrary grids);
- Narrow linewidth less than 100 kHz and offset-grid tuning greater than ± 6 GHz ideally suited for coherent mixing applications and new complex modulation formats; and
- Up to +15 dBm output power, with 8 dB power adjustment range.
- Equipped with Panda polarization maintaining fiber.




Figure 1. Graphical user interface

The 77-Series Optical Test Instruments

Targeted for high test throughput, lowest cost-per-channel, and narrow footprint, all members of Agilent's 77-Series optical test instruments are built on a common platform and a common PC-based user interface. A complete set of control interfaces including LAN, USB2.0 and GPIB simplifies integration with manufacturing control systems. Code compatible to Agilent's Lightwave Measurement System modules, the new instrument generation can serve as plug-in replacements in existing test solutions.

All 77-series optical test instruments share:

- "just-enough-test" approach with lowest hardware overhead;
- LAN, USB and GPIB interfaces;
- Built-in international power supply;
- SCPI command set, compatible with existing instrument categories for easy drop-in replacement; and
- Agilent IO libraries and a PC-based graphical user interface.

The N77-Viewer: An easy-to-use graphical user interface

The N77's Window's based graphical user interface offers flexible and extensive control of the instrument.

- Easy switching between channels with tabs.
- Overview window with all channels at a glance.
- Two instrument configurations can be stored and recalled.
- Turn on and off the laser output with one click.
- Choose between setting a laser's wavelength, frequency, channel or its output power.

Technical Specifications

Specifications apply to wavelengths on the 50 GHz ITU-T grid, after warm up.

Parameter	Agilent N7711A, N7714A	
Wavelength	Options #210, #222, #240	Options #201, #222, #204
Wavelength (frequency) range	1527.60 nm to 1565.50 nm (196.25 THz to 191.50 THz)	1570.01 nm to 1608.76 nm (190.95 THz to 186.35 THz)
Fine tuning range	Typical ± 6 GHz	
Fine tuning resolution	Typical 1 MHz	
Absolute wavelength (frequency) accuracy	± 22 pm (± 2.5 GHz)	
Relative wavelength (frequency) accuracy	± 12 pm (± 1.5 GHz)	
Wavelength (frequency) repeatability	Typical ± 2.5 pm (± 0.3 GHz) ²	
Wavelength (frequency) stability	Typical ± 2.5 pm (± 0.3 GHz), 24 hours ²	
Tuning time	Typical < 30 sec ³	
Optical power		
Max. output power	+13.5 dBm Typical +15 dBm	
Power stability	Typical ± 0.03 dB over 24 hours ²	
Power flatness	Typical ± 0.2 dB (full wavelength range)	
Power repeatability	Typical ± 0.08 dB ²	
Spectral		
Linewidth	Typical < 100 kHz (SBS suppression off)	
Side mode suppression ratio (SMSR)	Typical 50 dB	
Source spontaneous emission (SSE)	Typical 50 dB/ 1 nm ¹ Typical 60 dB/ 0.1 nm ¹	
Relative intensity noise (RIN)	Typical -145 dB/Hz ¹ (10 MHz to 40 GHz)	

1. At maximum specified output power, as specified per wavelength range

2. At constant temperature ± 0.5 K


3. Including power stabilization

Supplementary Performance Characteristics, Non-warranted

Parameter	Agilent N7711A, N7714A
Grid spacing	100 GHz, 50 GHz, 25 GHz, or arbitrary grid
Output power	
Power attenuation range	8 dB
Power setting resolution	0.1 dB
Residual output power (shutter closed)	-45 dBm
Stimulated Brillouin scattering	
SBS suppression FM p-p modulation range	0 GHz to 1 GHz
SBS suppression dither frequency	20.8 kHz

General Characteristics

Parameter	Agilent N7711A, N7714A
Connectivity	FC/APC angled (option #072) or FC/PC straight (option #071) connector interface
Fiber type	9/125 µm panda PMF
Laser safety	Class 1M
Recommended recalibration period	24 months
Operating conditions	+10 °C to +35 °C < 80% relative humidity, non-condensing
Altitude	Max 2000 m
Pollution protection	Designed for pollution detection degree 2
Storage conditions	-40 °C to +70 °C < 80% relative humidity, non-condensing
Form factor	One rack unit, ½ 19" width
Dimensions (H x W x D)	43 mm x 212 mm x 372 mm
Weight	3.8 kg (6 lbs)
Front panel	Status LEDs, laser on/off buttons, line power on/off switch
Connectivity, rear panel	USB 2.0, LAN 10/100 Mbit/s, GPIB
User interface	PC user interface application, SCPI commands, Agilent IO libraries
Power consumption	AC 100-240 V ±10%, 50 Hz/60 Hz
Laser safety information	All laser sources specified by this data sheet are classified as Class 1M according to IEC 60825-1 (2007).



All laser sources comply with 21 CFR 1040.10 except for deviations pursuant to Laser Notice No. 50, dated 2007, June 24.

Ordering Information

All systems have 1 year warranty

Model number	
N7711A	Tunable laser source, 1 port
N7714A	Tunable laser source, 4 ports

Connector interface option	
-071	Straight connector interface, PMF
-072	Angled connector interface, PMF

Wavelength (frequency) option	
N7711A	
-210	C-band laser
-201	L-band laser
N7714A	
-240	4 C-band lasers
-204	4 L-band lasers
-222	2 C-band lasers and 2 L-band lasers

Accessories	
N7744-100	Rack mount kit for 1 or 2 units

Warranty	
All systems have 1 year warranty	
R-51B-001-3C	1 year return-to-Agilent warranty extended to 3 years
R-51B-001-5C	1 year return-to-Agilent warranty extended to 5 years

Calibration	
R-50C-011-3	Agilent calibration upfront support plan 3 years coverage
R-50C-011-5	Agilent calibration upfront support plan 5 years coverage



Agilent Email Updates

www.agilent.com/find/emailupdates

Get the latest information on the products and applications you select.



Agilent Direct

www.agilent.com/find/agilentdirect

Quickly choose and use your test equipment solutions with confidence.



www.lxistandard.org

LXI is the LAN-based successor to GPIB, providing faster, more efficient connectivity. Agilent is a founding member of the LXI consortium.

Agilent Channel Partners

www.agilent.com/find/channelpartners

Get the best of both worlds: Agilent's measurement expertise and product breadth, combined with channel partner convenience.



Agilent Advantage Services is committed to your success throughout your equipment's lifetime. We share measurement and service expertise to help you create the products that change our world. To keep you competitive, we continually invest in tools and processes that speed up calibration and repair, reduce your cost of ownership, and move us ahead of your development curve.

www.agilent.com/find/advantageservices



www.agilent.com/quality

www.agilent.com
www.agilent.com/find/tls

For more information on Agilent Technologies' products, applications or services, please contact your local Agilent office. The complete list is available at:

www.agilent.com/find/contactus

Americas

Canada	(877) 894 4414
Brazil	(11) 4197 3500
Latin America	305 269 7500
Mexico	01800 5064 800
United States	(800) 829 4444

Asia Pacific

Australia	1 800 629 485
China	800 810 0189
Hong Kong	800 938 693
India	1 800 112 929
Japan	0120 (421) 345
Korea	080 769 0800
Malaysia	1 800 888 848
Singapore	1 800 375 8100
Taiwan	0800 047 866
Thailand	1 800 226 008

Europe & Middle East

Austria	43 (0) 1 360 277 1571
Belgium	32 (0) 2 404 93 40
Denmark	45 70 13 15 15
Finland	358 (0) 10 855 2100
France	0825 010 700*
	*0.125 €/minute
Germany	49 (0) 7031 464 6333
Ireland	1890 924 204
Israel	972-3-9288-504/544
Italy	39 02 92 60 8484
Netherlands	31 (0) 20 547 2111
Spain	34 (91) 631 3300
Sweden	0200-88 22 55
Switzerland	0800 80 53 53
United Kingdom	44 (0) 118 9276201

Other European Countries:

www.agilent.com/find/contactus

Revised: July 8, 2010

Product specifications and descriptions in this document subject to change without notice.

© Agilent Technologies, Inc. 2010
Printed in USA, July 23, 2010
5990-5512EN



Agilent Technologies